

Rackmount KVM Drawer with High Density USB DVI KVM Switch

RACKMUX®

How to Control up to sixteen single link DVI-enabled USB computers.

- Available with forward-folding 17" (432 mm) TFT/LCD DVI monitor.
 - Video Resolution: 1280x1024
 - Optional high resolution 1920x1200 WUXGA 17.1" monitor available.
- Available with a 4-, 8-, or 16-port USB DVI KVM switch.
 - Control up to 16 USB enabled computers with single link DVI outputs.
- Torque-friction hinges-monitor does not wobble, spring, or slam shut.
- Compact, heavy-duty tactile keyboard with 17-key numeric keypad.
- Rugged steel construction with durable powder coat finish.
- LCD auto-shutoff in closed position.
- Drawer locks into place when open to prevent it from sliding out of the rack.
- Cabling runs are simplified with NTI's high density KVM switch cables.
- Keyboard available in: English(US).



RACKMUX-D17-N-16DVIHD

- **Control 16 DVI USB Computers in 1RU**
- **Optional hi-res 1920x1200 17.1" LCD**

The RACKMUX® KVM Drawer with Built-In High Density USB DVI KVM Switch combines a rackmount LCD monitor, keyboard, touchpad mouse and a USB DVI KVM switch in a space-saving 1RU industrial strength drawer.

Specifications

Power

- 110 or 220 VAC at 50 or 60 Hz via IEC connector.
- Power Consumption:
 - RACKMUX-D17HR-N-8DVIHD: 40W

Dimensions

- WxDxH: 19x23.9x1.75 inches. (483x607x44 millimeters)
 - Handle adds an additional 1.5" to the depth when monitor is in closed position.
- Drawer is adjustable to various rack depths from 24" (610 mm) deep to 40" (1,016 mm) deep.
- Drawer locks into place when open to prevent it from sliding in and out of the rack.
- Rack ears are available for two post style telco rack mounting, select part number RL-T15-TEL.

Regulatory Approvals

- CE, RoHS
- TAA compliant

Environmental

- Operating temperature: 32 to 104°F (0 to 40°C).
- Storage temperature: -4 to 140°F (-20 to 60°C).
- Operating and Storage Relative Humidity: 20 to 90% non-condensing RH.

Warranty

- Two years

Additional Information

- Rackmount DVI USB + PS2 KVM Drawer Specifications www.networktechinc.com/kvm-drawer-dvi.html
- UNIMUX™ High Density USB DVI KVM switch www.networktechinc.com/srvsw-usb-dvi.html

Rackmount KVM Drawer with High Density USB DVI KVM Switch RACKMUX®

How to Control up to sixteen single link DVI-enabled USB computers.

KVM Drawers with High Density USB DVI KVM Switch			
NTI Part #	Screen Size (inches)	# of CPUs	Video Resolution
RACKMUX-D17-N-4DVIHD	17	4	1280x1024
RACKMUX-D17-N-8DVIHD	17	8	1280x1024
RACKMUX-D17-N-16DVIHD	17	16	1280x1024
RACKMUX-D17HR-N-4DVIHD	17.1	4	1920X1200
RACKMUX-D17HR-N-8DVIHD	17.1	8	1920X1200
RACKMUX-D17HR-N-16DVIHD	17.1	16	1920X1200