

Remote Power Reboot Switch

ENVIROMUX®

Feature Comparison



Product Feature	PWR-RMT-RBT-LC	PWR-RMT-RBT-515R-LC
Input Connector	IEC 320 C14	IEC 320 C14
Output Connector	IEC 320 C13	NEMA 5-15R
Power	105 to 240 VAC at 50 or 60 Hz	125 to 250 VAC at 50 or 60 Hz
Fuse	N/A	10A
Remote Power Control Options	4-Options	4-Options
On	✓	✓
Off	✓	✓
Reboot	✓	✓
Auto-Schedule	✓	✓
Control Methods	3 Methods	2-Methods
Web-Interface	✓	✓
Telnet	✓	N/A
DxP (Dataprobe-Exchange Protocol)	✓	N/A
iPhone/Android App	N/A	✓
Ethernet Ports	10/100 Base-T	10/100 Base-T
Monitor (Ping) IP Devices	✓ – up to 2 network devices per unit	N/A – Checks network connection and can automatically reboot device if there is no response
Local Ping	✓ – automatically reboots device if there is no response	N/A
Remote Ping	✓ – pings a remote host and powers up alarm or connected device when there is no response	N/A
Protocols Supported	HTTP, TCP/IP, DHCP, Auto-ping TCP, Telnet, DxP	HTTP, TCP/IP, UDP, Dynamic DNS, DNS Client, DHCP
Operating Temperature	32 to 122°F (0 to 50°C)	32° to 140° F (0° C to 60° C)
Operating/storage relative humidity	Unspecified	10 to 90% non-condensing RH
Cables Included	<ul style="list-style-type: none"> • 6 ft (2m) CAT5 cable • PWR-RMT-RBT-LC: 12A US line cord and extension cord • PWR-RMT-RBT-LC10A: 10A country-specific line cord and extension cord 	<ul style="list-style-type: none"> • 6 ft (2m) CAT5 cable • 10A US line cord and extension cord
Dimensions WxDxH	2.0x3.2x4.2 in (60x82x107 mm)	3.63x3.38x2.38 in (92x86x60 mm)
Regulatory Approvals	CE, UL, cUL, FCC, RoHS	FCC
Expandable	✓	✓
Web-Interface	Control unlimited number of units	N/A
iPhone/Android App	N/A	<ul style="list-style-type: none"> • Control unlimited number of units (restricted by storage space) • Up to 4 devices can control one unit