

### Alert & Communication Accessories

#### Automatic Voice/Pager Dialer Systems

##### Automatic Voice/Pager Dialer System, Calls 8 Phone Numbers, 4 Input Channels



**ENVIROMUX-AVDS**

- Calls up to 8 telephones, pagers, or cell phones when a sensor goes out of range of a configurable threshold.
- Program up to 4 separate input channels.
- Stores up to 4 outgoing voice messages. Create a message for 4 different types of alarms.

##### Automatic Voice Dialer System, Powered, Calls 5 Phone Numbers, 3 Input Channels



**ENVIROMUX-AVDS-LC1P**

- Calls up to 5 telephones or cell phones when a sensor goes out of range of a configurable threshold.
- Program 3 input channels.
- Create a recorded voice message of up to 20 seconds.

##### Low-Cost Automatic Voice Dialer System, CE, Calls 4 Phone Numbers, 1 Input Channel



**ENVIROMUX-AVDS-CELC**

- Calls up to 4 telephones or cell phones when a sensor goes out of a configurable threshold.
- Program 1 input channel with individual activation options.
- Create a recorded voice message of up to 20 seconds.

##### GSM Automatic Voice Dialer



**ENVIROMUX-AVDS-GSM**

- Ideal for remote places without conventional phone lines.
- Calls or sends SMS up to 8 telephone or cell phone numbers when a sensor goes out of range of a configurable threshold.
- Program one input channel with individual activation options.
- Stores one outgoing voice message of up to 20 seconds and one SMS message of up to 70 bytes.

#### Internet Tablets

##### 7-inch Tablet with ENVIROMUX® Android App



**ENVIROMUX-TAB7**

- Use tablet network interface to view real-time sensor values and alert statuses of sensors/digital inputs/IP devices outside of the server room.
- Grants full control of the unit through the web interface with admin/user log in.
- Display Size: 7".

- ENVIROMUX® Android App pre-installed
  - Sensor value and alert status pages feature large fonts for viewing from a distance.
  - Display individual or group sensor values at a configurable scan rate - updated in real time.

#### Modems

##### Industrial USB 3G Modem



**ENVIROMUX-3GU-IND**

- Sends SMS text messages to a pager or cell phone when a sensor goes out of range of a configurable threshold.
  - SIM card supporting SMS messaging required (not included).
  - Ideal for harsh environments and high temperatures up to 176°F (80°C).
  - Supports 2G and 3G digital cellular standards.
  - USB 2.0 interface.
- 3G network band:
    - HSDPA (WCDMA/FDD) 850/1900/2100 MHz
  - 2G network band:
    - GSM/GPRS/EDGE-850/900/1800/1900 MHz.

##### USB 3G Modem



**ENVIROMUX-3GU-4**

- Sends SMS text messages to a pager or cell phone when a sensor goes out of range of a configurable threshold.
- SIM card supporting SMS messaging required (not included).
- 3G network band: HSPA+/HSUPA/HSDPA/HSPA/UMTS(WCDMA)-2100 MHz.
- 2G network band: GSM/GPRS/EDGE-850/900/1800/1900 MHz

## Alert & Communication Accessories

### IP Surveillance Cameras

#### Wireless/Wired IP Surveillance Camera



**ENVIROMUX-IPCAM**

- View the camera from the ENVIROMUX web interface, camera web interface, included software, or with a compatible cell phone.
- With the ENVIROMUX-2D/5D/16D, a triggered snapshot can be forwarded in alert e-mails or stored locally on a connected flash drive.
- Video Streaming: simultaneous Motion JPEG
- Frame rate:
  - 20fps at 640x480
  - 30fps at 320x240
- Lens: F2.8, 3.15 mm

#### High-Definition Wireless/Wired Day/Night IP Camera



**ENVIROMUX-IPCAM-WHN**

- View the camera from the ENVIROMUX web interface, camera web interface, included software, or with a compatible cell phone.
- Two-way Audio with built-in microphone and stereo audio output for external speaker.
- 1/4" CMOS sensor with 4x digital zoom.
- Video streaming: H.264, MPEG4, MJPEG
- Frame rate: 30 fps up to 1280x720.
- Lens: F2.0, 3.35 mm.
- Supports wireless 802.11 b/g/n and 802.3 3u/3x

#### High-Definition Wired Day/Night Outdoor IP Dome Camera with Power over Ethernet (PoE)



**ENVIROMUX-IPCAM-DHNPO-P**

- View the camera from the ENVIROMUX web interface, camera web interface, included software, or with a compatible cell phone.
- Night Vision IR Range: 98 feet (30 m) 1/4" CMOS sensor with 4x digital zoom.
- Lens: F2.0; 2.8 mm fixed
- 10/100 Mbps Ethernet port for wired connections.
- System compatibility: ONVIF, PSIA, CGI, ISAPI
- Power:
  - Input: 100 to 240 VAC at 50 or 60 Hz
  - Output: 12 VDC, 1A external power adapter (included)
  - Max consumption: 5 W
  - Power over Ethernet standards supported: IEEE 802.3af
- 2MP resolution @ 30 fps
  - Supports 1920x1080, 1280x960, 1280x720

#### Wireless/Wired Day/Night IP Camera



**ENVIROMUX-IPCAM-WN**

- View and control the camera from the ENVIROMUX web interface, the camera web interface, included software, or with a compatible cell phone.
- With the ENVIROMUX-2D/5D/16D, a triggered snapshot can be forwarded in alert e-mails.
- Two-way Audio with built-in microphone and audio speaker.
- IR-LED for night vision up to 15 ft (4.6 m) and provides minimum 1.0 Lux for low light environments.
- 1/5" CMOS sensor with 4x digital zoom.
- Video streaming: H.264, MJPEG.
- Frame rate: 30 fps at 640x480, 320x240, and 160x120.
- Lens: 3.15mm (0.12 in).
- Supports wireless 802.11n/g.

#### Wired Day/Night PTZ IP Camera with Power over Ethernet (PoE)



**ENVIROMUX-IPCAM-NPOE**

- View and control the camera from the ENVIROMUX web interface, the camera web interface, included software, or with a compatible cell phone.
- A triggered snapshot can be forwarded in alert e-mails.
- Lens: F1.5, 4 mm (0.16 in).
- 1/4" CMOS sensor with 4x digital zoom.
- Frame rate: 30 fps at 1280x800 (WXGA), 640x400, 320x192, and 160x96.
- Supports Power over Ethernet (PoE) – power supply not required.

## Alert & Communication Accessories

### Sirens

#### Rugged Miniature Piezo Alarm, 103 dB

**ENVIROMUX-BEEP1-x**

- Output level: 95 to 103 dB at 2 feet.
- Input voltage: 5-15VDC.
- Panel mount.
- Water, humidity and vibration resistant.
- Available lengths for included 2-wire cable: 1/10/50/100/200/400/600/800/1000 feet.

#### Miniature Piezo Buzzer, PCB Mount, 95 dB

**ENVIROMUX-BEEP2-x**

- Output level: 95 dB.
- Input voltage: 12VDC.
- PCB mount pins on 7.62 mm centers.
- Available lengths for included 2-wire cable: 1/10/50/100/200/400/600/800/1000 feet.

#### Piezo Siren, 108 dB

**ENVIROMUX-SRN-M**

- Output Level: 108 dB
- Input voltage: 6-12VDC

### Alarm Beacons

#### Alarm Beacon - Small: 2.75x1.69 in (70x43 mm)

**ENVIROMUX-BCN-R**

- Emits flashing red light when activated
- Flash Rate: 90 per minute
- Input voltage: 6 to 12VDC

#### Alarm Beacon - Large: 3.94x3.46 in (100x88 mm)

**ENVIROMUX-BCN-RL**

- Emits flashing red light when activated
- Flash Rate: 75 per minute
- Input voltage: 6 to 12VDC