RACKMOUNT USB KVM DRAWER WITH TOUCHPAD MOUSE

USB KVM Drawer provides space-saving convenient control.

RACKMUX-UW17 (Front and Back)

Features & Applications

The RACKMUX® USB KVM Drawer combines a rackmount LCD monitor, USB keyboard and touchpad mouse in a space-saving 1RU industrial strength drawer.

- Available with 15" or 17" Active Matrix LCD flat panel monitor.
- Equipped with On Screen Display (OSD).
- Compact, heavy-duty tactile keyboard.
- Security lock on front panel.
- Front panel conceals the unit when not in use.
- Designed to fit in a standard 19" rack/cabinet.
- Display automatically powers off when in closed position.
- Drawer locks into place when open to prevent it from sliding in and out of the rack.

Specifications

Hosts

- Compatible with USB-enabled PC, SUN or MAC computers.

Monitor

- 15" or 17" Active Matrix LCD flat panel monitor.
- 1024x768 video resolution for 15" monitor.
- 1280x1024 video resolution for 17" monitor.
- Supports Composite sync, H/V separate (TTL) sync. Does not support Sync on Green. Not compatible with all Sun Microsystems.
- Frequency:
  - Horzontal: 30 to 64 KHz for 15" drawers, and 30 to 82 kHz for 17" drawers.
  - Vertical: 50 to 75 Hz for both drawers.
- Viewing angle:
  - 15": Horizontal: 115°, Vertical: 115°
  - 17": Horizontal: 120°, Vertical: 120°
- OSD controls for brightness, contrast, phase, pitch, Horz- and Vert-center alignment, zoom and color adjustment.
- 250 nits brightness and 350:1 contrast ratio typical.
- Supports DDC1 and DDC2B protocols.

Devices

- 15" model: Female USB Type A connector.
- 17" model: Female USB Type B connector.
- "Gold Crosspoint" keyboard contacts ensure high reliability.
- 105-key keyboard.
- Keyboard available in multiple languages: English(US), English(UK), German, Italian, French, and Spanish.
- Two button touchpad mouse.

Cables

- 6-foot 15 HD VGA male to male cable included.
- 6-foot USB Type A male to male cable included for 15" model.
- 6-foot male USB Type A to male USB Type B cable included for 17" model.
- 6-foot DC power supply cable included.

Power

- 110 or 220 VAC at 50 or 60 Hz via AC Adapter.
- Power consumption:
  - 15" model: 20W
  - 17" model: 35W

Dimensions

- 15" drawer, WxDxH (in.): 19x20.1x1.75.
- 17" drawer, WxDxH (in.): 19x20.2x1.75.
- Drawer is adjustable to various rack depths.
  - 15" drawer ranges from 20.1" to 31.5".
  - 17" drawer ranges from 20.2" to 33.5".

Warranty

- Two years

Extension Rail Option

RACKMUX-EXT-RL

- Allows adjustments to various rack depths.
  - 15" drawer ranges from 24.1" to 34.8".
  - 17" drawer ranges from 26.1" to 36.8".

PS/2 KVM Drawers		
NTI Part#	Screen Size	Weight (lbs)
RACKMUX-UW15	15''	33
RACKMUX-UW17	17''	36