


## Allows two users to control one HDMI USB computer and three USB Devices

- Compatible with USB computers (PC, SUN, MAC)
- Built-in hub for multiple USB devices.
- Access one computer from multiple locations.
- Multiple users can enter data into the same program.
- Supports HDTV resolutions to 1080i, and up to 1920x1200 (WUXGA).
- Compliant with USB (low/full speed) standards.
- Compliant with HDMI 1.2, HDCP 1.1 and DVI 1.0 standards.
- Supports Plug-n-Play specifications.
- High quality, rugged steel construction with durable, powder-coat finish.



**VOPEX-USBH-2 (Front & Back)**

The VOPEX® HDMI USB KVM splitter with built-in USB hub allows two users (two USB keyboards, USB mice and HDMI monitors) to access one USB computer and up to three USB devices (printers, scanners, security cameras, etc.).

## Specifications

### Host Connection

- Female HDMI-A connector.
- Female USB Type B connector.
- Supports a USB computer (PC, SUN, MAC) with HDMI video.
- Multiplatform support: Windows 7/8/10/11, Windows Server 2008/2012/2016/2019/2022, Solaris, Linux, FreeBSD, and MAC OS 10/11/12.

### Monitor

- Female HDMI-A connectors.
- Supports HDTV resolutions to 1080i, and up to 1920x1200 (WUXGA).
- Compliant with HDMI 1.2, HDCP 1.1 and DVI 1.0 standards.

### Devices

- Female USB Type A connectors for connection of keyboard, mouse.
  - Compatible with most USB keyboards/mice, including Microsoft USB Intellimouse®, Logitech Cordless Elite Duo keyboard/mouse, Logitech MK345/MK735 wireless keyboard/mouse, Gyration keyboard/mouse and Crystal Vision keyboard with touchpad.
  - Keyboard and mouse are hot-pluggable.
  - Supports international keyboard layouts in auto-detection mode.
- Three female USB Type A connectors for connection of USB peripheral devices (printers, scanners, security cameras, etc.)
  - Does not support USB touchscreen monitors.
- Provides support for full-speed (12 Mbps) or low-speed (1.5 Mbps) USB devices.

### Power

- 100 to 240 VAC at 50 or 60 Hz via AC adapter. (Country specific AC adapter included.)

### MTBF

- 200,241 hours

### Dimensions

- WxDxH (in): 8.5x6.0x2.6

### Environmental

- Operating temperature: 32 to 100°F (0 to 38°C).
- Storage temperature: -22 to 140°F (-30 to 60°C).
- Operating/storage relative humidity: 17 to 90% non-condensing RH.

### Regulatory Approvals

- CE, RoHS
- TAA compliant

### Cables

- Use the included three-foot HDMI-A male-to-male single link cable to connect an HDMI source or display.
- Use DVI-HD-xM-MM cable to connect a DVI source or display (not included).
- One-meter male USB Type A to male USB Type B cable included.

## Control Modes

- Press **Mode** button to cycle through all four modes. LEDs indicate which mode is selected.
- **User 1 Mode**—only User 1 can type or move mouse.
- **User 2 Mode**—only User 2 can type or move mouse.
- **Inst Mode**—keyboard or mouse activates immediately
- **Delay Mode**—locked out user must wait five seconds after last keystroke or mouse movement occurs on active user.