

## Use one computer to display the same high-resolution image on numerous monitors – up to 256

- Supports VGA/SVGA UXGA/WUXGA monitors, including LCD flat panel monitors.
- 1920x1200 resolution with no degradation.
- Supports the DDC2B protocol.
- Burn-in monitors after repair.
- Ideal for classrooms, tradeshows, or digital signage where high quality video on multiple monitors is needed.



### VOPEX-8V-H VGA Video Splitter (Front & Back)

The VOPEX® VGA Video Splitter enables up to eight VGA monitors to be driven by a single computer. The same image can be displayed on up to 256 monitors by cascading. The DDC2B protocol is supported from Output-1.

## Specifications

### Video Input

- Male 15-pin HD input connector.
- Supports a PC, SUN or MAC with VGA video.
- Multiplatform support: Windows 7/8/10, Windows Server 2008/2012/2016/2019, Solaris, Linux, FreeBSD, and MAC OS 10/11. Maximum input levels for video: 1.45Vp-p.
- Input impedance: 75 Ohms.
- Supports Separate and Composite TTL level sync and Sync On Green.
- Sync input frequency ranges:
  - Horizontal: 15 to 130 kHz.
  - Vertical: 30 to 150 Hz.

### Video Output

- Female 15-pin HD output connectors.
- Crisp and clear 1920x1200 resolution.
- Bandwidth is 150 MHz.
- Maximum output levels for video: 1.45Vp-p.
- Output impedance: 75 Ohms.
- All outputs are individually buffered.
- All monitors must be able to support the highest resolution of the DDC monitor connected to Output-1.

### Environmental

- Operating temperature: 32 to 100°F (0 to 38°C)
- Storage temperature: -22 to 140°F (-30 to 60°C)
- Operating and storage relative humidity: 5 to 90% non-condensing RH.

### Power

- 100 to 240 VAC at 50 or 60 Hz.

#### Power Consumption

Model	Power (W)	Model	Power (W)
VOPEX-2V-H	5	VOPEX-4V-H	5
VOPEX-8V-H	5		

#### MTBF

NTI Part #	MTBF (hrs)	NTI Part #	MTBF (hrs)
VOPEX-2V-H	175,784	VOPEX-4V-H	153,392
VOPEX-8V-H	135,708		

### Regulatory Approvals

- RoHS
- TAA compliant

## Cables

- Extend 1920x1200 resolution to 50 feet (15 meters), and 1600x1200 to 100 feet (488x366 to 30 meters) with no degradation using NTI's VEXT-xx cables.
- 3-foot (0.91-meter) VGA cable included.

Use one computer to display the same high-resolution image on numerous monitors: up to 256

VGA Video Splitter Models		
NTI Part #	# of Ports	Size WxDxH (in.)
VOPEX-2V-H	2	4.9x5.2x1.7
VOPEX-4V-H	4	8x6.2x2.6
VOPEX-8V-H	8	8x6.2x2.6

## Configuration and Cable Illustration

